



AL

Alumex

ALUMINIUM BRIGHTNER AND RENOVATOR

- Very economical to use
- Begins working instantly, thus saving labor costs
- Can be diluted with up to 25 parts of water
- Dissolves even the toughest road film
- Removes dirt, deposits and diesel residues from highway trailers, trucks and other road vehicles
- Leaves no salts or deposits to streak



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Xintex is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Xintex products provide, relates only to the standard conditions of sale of this product. In no case Xintex can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

General Information

ALUMEX is a fast acting, non-streaking, liquid concentrate especially formulated to clean aluminium, stainless steel and galvanized surfaces. It effectively removes dirt, deposits and diesel residues from highway trailers, trucks and other road vehicles. ALUMEX can also be used for any aluminum or stainless steel surface that is exposed to the weather; as well as for removing scale and water residues from aluminum boats.

Due to its high concentration and quick brightening and cleaning power, ALUMEX is very economical in use and dissolves instantly even the toughest residues. Depending on the grade of pollution, ALUMEX can be diluted with up to 25 parts of water. Because of its special formulation, ALUMEX does not leave any residues or streaks and leaves a soft, glare free surface.

Technical Information



Form: liquid
Colour: red
Odour: characteristic
pH-value (at 20°C): 2.5
Initial boiling point: 100°C

Vapour pressure (at 20°C): 23 hPa
Density (at 20°C): 1,15 g/cm³
Solubility in water: completely miscible
Storage: frost-free
Shelf life: 36 months

Application and Use

- ALUMEX is specially designed for the use on truck fleets, truck washing operators, building construction and maintenance companies (for aluminum, stainless steel and galvanized structures)
- Dilute ALUMEX 1:3 to 1:25 with water, depending on the grade of pollution. Large surfaces should be cleaned in smaller parts in order to avoid too long contact with ALUMEX.
- Apply ALUMEX with a sprayer or if necessary with a brush or sponge.
- After cleaning the surface, rinse off with plenty of (hot) water
- NOTE: Do not use ALUMEX on aluminium frames for windows or mirrors as the product damages glass.

Article nr	Name	Content	Shelf Life	Catalog
X119025	Alumex	25l	see imprint + 36 months	SURFACE PROTECTION AND TREATMENT



TECH-MASTERS TRADING GMBH

Perfektastraße 55, 1230 Wien, Austria, Tel +43 (0) 1 / 867 29 07
Fax +43 (0) 1 / 867 29 93, E-Mail office@tech-masters-trading.com

WWW.XINTEX-GROUP.COM