according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 10 Jan 2025

Version: 4
Page 1/13

XINTEX
solutions for professionals

Aquatron 2001

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Aquatron 2001

Article No.:

X121200

UFI:

90SH-C3JQ-632H-RY3D

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

All-purpose cleaner without abrasives

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3 4653 Eberstalzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

| Hazard classes and hazard categories | Hazard statements | Classification procedure |
|---|--|--------------------------|
| Skin corrosion/irritation (Skin Corr. 1B) | H314: Causes severe skin burns and eye damage. | |

Additional information:

The product is not self-sustainingly combustible. Despite a flash point < 60 °C, classification as flammable is therefore not applicable.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



GHS05 Corrosion

Signal word: Danger

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 10 Jan 2025

Version: 4

Page 2/13



Aquatron 2001

Hazard components for labelling:

disodium metasilicate

| Hazard statements for health hazards | |
|--------------------------------------|--|
| H314 | Causes severe skin burns and eye damage. |

Supplemental hazard information: none

Precautionary statements Prevention

| P280 | Wear protective gloves/protective clothing and eye protection/face protection. | |
|--------------------|--|--|
| Precautionary stat | ements Response | |
| P301 + P330 + P331 | IF SWALLOWED: rinse mouth. Do NOT induce vomiting. | |
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. | |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. | |

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. The inhalation of dust/mist or aerosols causes irritation of the respiratory tract.

SECTION 3: Composition/information on ingredients

Immediately call a POISON CENTER.

* 3.2. Mixtures

P310

Hazardous ingredients / Hazardous impurities / Stabilisers:

| Product identifiers | Substance name | Concentration |
|--|---|-------------------|
| | Classification according to Regulation (EC) No 1272/2008 [CLP] | |
| CAS No.: 67-63-0 EC No.: 200-661-7 REACH No.: 01-2119457558-25 | propan-2-ol The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP]. Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, gases) > 25 ppmV ATE (inhalation, vapour) > 20 mg/L | 5 - < 10 Vol-% |
| CAS No.: 112-34-5 EC No.: 203-961-6 REACH No.: 01-2119475104-44 | 2-(2-butoxyethoxy)ethanol Substance with a community workplace exposure limit. Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, vapour) > 20 mg/L | 1 - < 5 Vol-% |
| CAS No.: 6834-92-0 EC No.: 229-912-9 Index No.: 014-010-00-8 REACH No.: 01-2119449811-37 | disodium metasilicate Met. Corr. 1 (H290), STOT SE 3 (H335), Skin Corr. 1B (H314) 1 Danger Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, dust/mist) > 5 mg/L | 1 - < 5 Vol-% |
| CAS No.: 68439-50-9 | Alkyl polyethoxilate Acute Tox. 4 (H302), Aquatic Chronic 3 (H412), Eye Dam. 1 (H318) Danger Acute Toxicity Estimate ATE (oral) 500 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, dust/mist) > 5 mg/L | 1 - < 5 Vol-% |
| Full toxt of H and FUH phra | Nonionic surfactants The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP]. | < 5 Vol-% |

Full text of H- and EUH-phrases: see section 16.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 10 Jan 2025

Version: 4 Page 3/13



Aquatron 2001

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Remove contaminated, saturated clothing immediately.

Following inhalation:

Provide fresh air.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap.

Take off contaminated clothing and wash it before reuse.

After eye contact:

Rinse immediately carefully and thoroughly with eye-bath or water.

Following ingestion:

Rinse mouth immediately and drink 1 glass of of water.

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water spray jet, alcohol resistant foam, Carbon dioxide, Extinguishing powder

Unsuitable extinguishing media:

Full water iet

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:

Carbon dioxide. Carbon monoxide

5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

General information:

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Emergency procedures:

Ventilate affected area.

6.1.2. For emergency responders

Personal protection equipment:

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 10 Jan 2025

Version: 4 Page 4/13



Aquatron 2001

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up:

Treat the recovered material as prescribed in the section on waste disposal.

Other information:

Collect in closed and suitable containers for disposal. Ventilate affected area.

6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Avoid contact with skin, eyes and clothes.

Do not mix with other chemicals.

Use personal protection equipment.

When using do not eat, drink, smoke, sniff.

Do not breathe gas/fumes/vapour/spray.

Use only in well-ventilated areas.

Fire prevent measures:

No special fire protection measures are necessary.

Advices on general occupational hygiene

Take off contaminated clothing.

Wash hands before breaks and after work.

When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Keep container tightly closed.

Hints on storage assembly:

No special measures are necessary.

Storage class (TRGS 510, Germany): 8B - Non-combustible corrosive substances

7.3. Specific end use(s)

Recommendation:

Cleaning agent

Industrial sector specific solutions:

Stripper, corrosive, solvent-based

GISCODE:

GG80

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 10 Jan 2025

Version: 4 Page 5/13



Aquatron 2001

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

| Limit value type (country of origin) | Substance name | Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark |
|--|--|--|
| MAK (AT) | propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7 | ② 800 ppm (2,000 mg/m³) ⑤ (max. 4x15 min./Schicht) |
| MAK (AT) | propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7 | ① 200 ppm (500 mg/m³) |
| MAK (AT) from 11 Sept 2007 | 2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6 | ② 15 ppm (101.2 mg/m³) ⑤ (max. 4x15 min./Schicht) |
| IOELV (EU) | 2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6 | ① 10 ppm (67.5 mg/m³) ② 15 ppm (101.2 mg/m³) |
| MAK (AT) from 11 Sept 2007 | 2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6 | ① 10 ppm (67.5 mg/m³) |

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

| Substance name | DNEL value | ① DNEL type② Exposure route |
|--|-------------------------|---|
| propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7 | 500 mg/m ³ | ① DNEL worker ② Long-term – inhalation, systemic effects |
| propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7 | 89 mg/m³ | DNEL Consumer Long-term – inhalation, systemic effects |
| propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7 | 888 mg/kg bw/ day | DNEL worker Long-term - dermal, systemic effects |
| propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7 | 319 mg/kg bw/ day | DNEL Consumer Long-term - dermal, systemic effects |
| propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7 | 26 mg/kg bw/ day | ① DNEL Consumer ② Long-term - oral, systemic effects |
| 2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6 | 40.5 mg/m ³ | DNEL Consumer Long-term – inhalation, systemic effects |
| 2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6 | 67.5 mg/m³ | ① DNEL worker ② Long-term – inhalation, local effects |
| 2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6 | 40.5 mg/m ³ | DNEL Consumer Long-term – inhalation, local effects |
| 2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6 | 101.2 mg/m ³ | DNEL worker Acute - inhalation, local effects |

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 **Print date:** 10 Jan 2025

Version: 4 Page 6/13



Aquatron 2001

| Substance name | DNEL value | ① DNEL type | |
|--|------------------------|--|--|
| | | ② Exposure route | |
| 2-(2-butoxyethoxy)ethanol | 60.7 mg/m ³ | ① DNEL Consumer | |
| CAS No.: 112-34-5 EC No.: 203-961-6 | | ② Acute - inhalation, local effects | |
| 2-(2-butoxyethoxy)ethanol | 83 mg/kg bw/ | ① DNEL worker | |
| CAS No.: 112-34-5 EC No.: 203-961-6 | day | ② Long-term - dermal, systemic effects | |
| 2-(2-butoxyethoxy)ethanol | 50 mg/kg bw/ | ① DNEL Consumer | |
| CAS No.: 112-34-5 EC No.: 203-961-6 | day | ② Long-term - dermal, systemic effects | |
| 2-(2-butoxyethoxy)ethanol | 6.25 mg/kg | ① DNEL Consumer | |
| CAS No.: 112-34-5 EC No.: 203-961-6 | | ② Long-term - oral, systemic effects | |
| 2-(2-butoxyethoxy)ethanol | 5 mg/kg bw/ | ① DNEL Consumer | |
| CAS No.: 112-34-5 EC No.: 203-961-6 | day | ② Long-term - oral, systemic effects | |
| Substance name | PNEC Value | ① PNEC type | |
| propan-2-ol CAS No.: 67-63-0 | 140.9 mg/L | ① PNEC aquatic, freshwater | |
| EC No.: 200-661-7 | | | |
| propan-2-ol | 140.9 mg/L | ① PNEC aquatic, marine water | |
| CAS No.: 67-63-0 EC No.: 200-661-7 | | | |
| propan-2-ol | 2,251 mg/L | ① PNEC sewage treatment plant | |
| CAS No.: 67-63-0 EC No.: 200-661-7 | | | |
| propan-2-ol | 552 mg/kg | ① PNEC sediment, freshwater | |
| CAS No.: 67-63-0 | | | |
| EC No.: 200-661-7 propan-2-ol | 552 mg/kg | ① PNEC sediment, marine water | |
| CAS No.: 67-63-0 | 332 mg/kg | FNEC Sediment, marine water | |
| EC No.: 200-661-7 | | | |
| propan-2-ol CAS No.: 67-63-0 | 28 mg/kg | ① PNEC soil | |
| EC No.: 200-661-7 | | | |
| propan-2-ol | 140.9 mg/L | ① PNEC aquatic, intermittent release | |
| CAS No.: 67-63-0 EC No.: 200-661-7 | | | |
| 2-(2-butoxyethoxy)ethanol | 1.1 mg/L | ① PNEC aquatic, freshwater | |
| CAS No.: 112-34-5 | | | |
| EC No.: 203-961-6 2-(2-butoxyethoxy)ethanol | 0.11 mg/L | ① PNEC aquatic, marine water | |
| CAS No.: 112-34-5 | 3.11 mg/L | S FINEC aquatic, mailine water | |
| EC No.: 203-961-6 | | | |
| 2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 | 200 mg/L | ① PNEC sewage treatment plant | |
| EC No.: 203-961-6 | | | |
| 2-(2-butoxyethoxy)ethanol | 4.4 mg/kg | ① PNEC sediment, freshwater | |
| CAS No.: 112-34-5 EC No.: 203-961-6 | | | |
| 2-(2-butoxyethoxy)ethanol | 0.44 mg/kg | ① PNEC sediment, marine water | |
| CAS No.: 112-34-5 EC No.: 203-961-6 | | | |
| 2-(2-butoxyethoxy)ethanol | 0.32 mg/kg | ① PNEC soil | |
| CAS No.: 112-34-5 EC No.: 203-961-6 | | | |
| 2-(2-butoxyethoxy)ethanol | 56 mg/kg | ① PNEC secondary poisoning | |
| CAS No.: 112-34-5 EC No.: 203-961-6 | | | |
| | | l en / AT | |

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 10 Jan 2025

Version: 4 Page 7/13



Aquatron 2001

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No information available.

8.2.2. Personal protection equipment





Eye/face protection:

Wear eye protection/face protection. (EN 166)

Skin protection:

Hand protection:

Wear gloves for protection against chemicals according to EN 374. (Breakthrough time: >10 min)

Suitable material: NBR (Nitrile rubber)
Thickness of the glove material >= 0,1 mm

A list of suitable makes with detailed information on wearing time is available on request.

Diluted application solutions <= 1%:

Protective gloves may be dispensed with, provided equivalent protective measures are taken, taking into account increased skin exposure due to wet work (e.g. use of suitable skin protection ointments).

Body protection: Wear suitable work clothing.

Respiratory protection:

When using the HD method or spraying over large areas: combination filter A1/P2 (EN 143, EN 14387). Use only in well-ventilated areas.

In case of inadequate ventilation wear respiratory protection.

Thermal hazards:

No further relevant information available.

8.2.3. Environmental exposure controls

Section 6: Accidental Release Measures

SECTION 9: Physical and chemical properties

st 9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Colour: light blue

Odour: characteristic **flammability:** No data available

Safety relevant basis data

| Parameter | Value | at °C | Method Remark |
|--|-------------------|-------|-------------------|
| | | | © Kellidi k |
| pH | 13 - 14 | 20 °C | |
| Melting point | ≈ 0 °C | | |
| Freezing point | ≈ 0 °C | | |
| Initial boiling point and boiling range | ≈ 100 °C | | |
| Flash point | 43 °C | | |
| Evaporation rate | No data available | | |
| Auto-ignition temperature | No data available | | |
| Upper/lower flammability or explosive limits | No data available | | |
| Vapour pressure | No data available | | |
| Vapour density | No data available | | |
| Density | 1.03 g/cm³ | 20 °C | |
| Bulk density | not applicable | | |

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 10 Jan 2025

Version: 4 Page 8/13



Aquatron 2001

| Parameter | Value | | ① Method② Remark |
|---------------------|------------------------|-------|---|
| Water solubility | completely miscible | | |
| Dynamic viscosity | < 10 mPa* s | 25 °C | |
| Kinematic viscosity | No data available | | |

9.2. Other information

Sustaining combustion: Not sustaining combustion.

SECTION 10: Stability and reactivity

10.1. Reactivity

Exothermic reaction with: Acid

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Acid

10.4. Conditions to avoid

The product is stable under storage at normal ambient temperatures.

10.5. Incompatible materials

Acid

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

st \mid 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7 **LD₅₀ oral:** >2,000 mg/kg (Rat) LD_{50} dermal: >2,000 mg/kg (Rat) LC₅₀ Acute inhalation toxicity (gas): >25 ppmV 4 h (Rat) LC₅₀ Acute inhalation toxicity (vapour): >20 mg/L 6 h (Rat) **2-(2-butoxyethoxy)ethanol** CAS No.: 112-34-5 EC No.: 203-961-6 **LD₅₀ oral:** >2,000 mg/kg (Rat) **LD₅₀ dermal:** >2,000 mg/kg (Rat) LC₅₀ Acute inhalation toxicity (vapour): >20 mg/L (Rat) disodium metasilicate CAS No.: 6834-92-0 EC No.: 229-912-9 **LD₅₀ oral:** >2,000 mg/kg (Rat) LD_{50} dermal: >2,000 mg/kg (Rat) LC₅₀ Acute inhalation toxicity (dust/mist): >5 mg/L Alkyl polyethoxilate CAS No.: 68439-50-9 **LD₅₀ oral:** 500 mg/kg (Rat) **LD₅₀ dermal:** >2,000 mg/kg (Rat) LC₅₀ Acute inhalation toxicity (dust/mist): >5 mg/L (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 10 Jan 2025

Version: 4 Page 9/13



Aquatron 2001

Skin corrosion/irritation:

Causes severe skin burns and eye damage.

Serious eye damage/irritation:

Causes severe skin burns and eye damage.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause respiratory irritation.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties:

No information available.

 LC_{50} : >1 mg/L 4 d (fish)

EC₅₀: >1 mg/L 2 d (crustaceans)
ErC₅₀: >1 mg/L (Algae/water plant)

SECTION 12: Ecological information

* 12.1. Toxicity

| propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7 |
|---|
| LC ₅₀ : >1,000 mg/L 4 d (fish) |
| EC₅₀: >1,000 mg/L 2 d (crustaceans) |
| LC ₅₀ : 9,640 mg/L 4 d (fish, Pimephales promelas) |
| LC ₅₀ : 9,714 mg/L 1 d (Daphnia magna) |
| EC ₅₀ : >100 mg/L (Algae/water plant, Bacteria) |
| LOEC: 1,000 mg/L (Alge) |
| EC ₅₀ : >100 mg/L 2 d (crustaceans, Daphnia magna) |
| ErC ₅₀ : >100 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus) |
| LOEC: 1,000 mg/L (Algae/water plant, Algae) |
| 2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6 |
| LC ₅₀ : 2,780 mg/L 4 d (fish, Pimephales promelas) |
| EC ₅₀ : 4,950 mg/L 2 d (crustaceans, Daphnia magna (Big water flea)) |
| ErC ₅₀ : >100 mg/L (Algae/water plant, Scenedesmus subspicatus) |
| EC ₅₀ : >100 mg/L 2 d (Daphnia magna) OECD 202 |
| ErC ₅₀ : >100 mg/L (Algae/water plant, Scenedesmus sp.) OECD 201 |
| disodium metasilicate CAS No.: 6834-92-0 EC No.: 229-912-9 |
| LC ₅₀ : 210 mg/L 4 d (fish, Danio rerio) |
| EC ₅₀ : 1,700 mg/L 2 d (crustaceans, Daphnia magna) |
| Alkyl polyethoxilate CAS No.: 68439-50-9 |

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 10 Jan 2025

Version: 4 Page 10/13



Aquatron 2001

12.2. Persistence and degradability

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Biodegradation: Yes, rapidly

Remark: Readily biodegradable (according to OECD criteria).

2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6

Biodegradation: Yes, rapidly

Remark: Readily biodegradable (according to OECD criteria).

Alkyl polyethoxilate CAS No.: 68439-50-9

Biodegradation: Yes, rapidly

Remark: Readily biodegradable (according to OECD criteria).

Biodegradation:

The surfactants contained in this mixture comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

12.3. Bioaccumulative potential

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Log Kow: 0.05

2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6

Log Kow: 0.56

Accumulation / Evaluation:

No indication of bioaccumulation potential.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Results of PBT and vPvB assessment: —

2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6

Results of PBT and vPvB assessment: —

disodium metasilicate CAS No.: 6834-92-0 EC No.: 229-912-9

Results of PBT and vPvB assessment: —
Alkyl polyethoxilate CAS No.: 68439-50-9

Results of PBT and vPvB assessment: —

Nonionic surfactants

Results of PBT and vPvB assessment: -

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation. Delivery to an approved waste disposal company.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV Waste code product

07 06 01 * aqueous washing liquids and mother liquors

*: Evidence for disposal must be provided.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 10 Jan 2025

Version: 4 Page 11/13



Aquatron 2001

Waste code packaging

15 01 02 Plastic packaging

Waste treatment options

Appropriate disposal / Package:

Non-contaminated packages may be recycled.

SECTION 14: Transport information

| • | | | | |
|--|---|---|--|--|
| Land transport (ADR/RID) | Inland waterway craft (ADN) | Sea transport (IMDG) | Air transport (ICAO-TI / IATA-DGR) | |
| 14.1. UN number or | ID number | • | | |
| UN 1719 | UN 1719 | UN 1719 | UN 1719 | |
| 14.2. UN proper ship | ping name | | | |
| CAUSTIC ALKALI LIQUID, N.O.S. (disodium metasilicate) | CAUSTIC ALKALI LIQUID, N.O.S. (disodium metasilicate) | CAUSTIC ALKALI LIQUID, N.O.S. (disodium metasilicate) | CAUSTIC ALKALI LIQUID, N.O.S. (disodium metasilicate) | |
| 14.3. Transport haza | rd class(es) | | | |
| 8 | 8 | 8 | 8 | |
| 14.4. Packing group | | | • | |
| III | III | III | III | |
| 14.5. Environmental | hazards | | | |
| No | No | No | No | |
| 14.6. Special precau | tions for user | | | |
| Special Provisions: 274 | Special Provisions: 274 | Special Provisions: 223 274 | Special Provisions: A3 A803 | |
| Limited quantity (LQ): 5 L | Limited quantity (LQ): 5 L | Limited quantity (LQ): 5 L | Limited quantity (LQ): Y841 | |
| Excepted Quantities (EQ): | Excepted Quantities (EQ): | Excepted Quantities (EQ): | Excepted Quantities (EQ): E1 | |
| Hazard identification number (Kemler No.): 80 Classification code: C5 Tunnel restriction code: (E) | Classification code: C5 | EmS-No.: F-A, S-B | Remark: IATA Packing Instructions - Passenger: 852 IATA Maximum Quantity - Passenger: 5 L IATA- Verpackungsanweisung - Cargo: 856 IATA Maximum Quantity - Cargo: 60 L | |

14.7. Maritime transport in bulk according to IMO instruments not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Restrictions on use (REACH, Annex XVII) Entry 3, Entry 40, Entry 55, Entry 75

Other regulations (EU):

This product is not assigned to a hazard category.

en / AT

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 10 Jan 2025

Version: 4 Page 12/13 XINIEX

solutions for professionals

Aquatron 2001

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 5.5 Vol-%

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

15.3. Additional information

Regulation (EC) No. 648/2004 [Detergents regulation]

SECTION 16: Other information

16.1. Indication of changes

| 3.2. | Mixtures |
|-------|--|
| 3.2. | Mixtures |
| 8.1. | Control parameters |
| 9.1. | Information on basic physical and chemical properties |
| 11.1. | Information on hazard classes as defined in Regulation (EC) No 1272/2008 |
| 12.1. | Toxicity |
| 14.3. | Transport hazard class(es) |
| 16.1. | Indication of changes |
| 16.2. | Abbreviations and acronyms |

* 16.2. Abbreviations and acronyms

| ACGIH | American Conference of Governmental Industrial Hygienists | |
|-------|---|--|

| ADN | European A | Agreement concernii | ng the | International | Carriage of | Dangerous | Goods by Inland |
|-----|------------|---------------------|--------|---------------|-------------|-----------|-----------------|
| | | | | | | | |

Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging

DNEL derived no-effect level EC₅₀ Effective Concentration 50%

EN European Standard ES Exposure scenario

EWC European Waste Catalogue

ICAO International Civil Aviation Organization
IMDG International Maritime Dangerous Goods
IMO International Maritime Organization

KG body weight

LC₅₀ Lethal (fatal) Concentration 50%

LD₅₀ Lethal (fatal) Dose 50%

MAK Maximum concentration in the workplace air (CH)

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety & Health

OECD Organisation for Economic Cooperation and Development

OSHA Occupational Safety & Health Administration PBT persistent and bioaccumulative and toxic

PC Product category

PNEC Predicted No Effect Concentration

PROC Process Category

REACH Registration, Evaluation and Authorization of Chemicals RID Dangerous goods regulations for transport by rail

SCL Specific concentration limit

TRGS Technische Regeln für Gefahrstoffe

UN United Nations

VOC Volatile organic compounds ZNS central nervous system

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 10 Jan 2025

Version: 4

Page 13/13



Aquatron 2001

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

| Hazard classes and hazard categories | Hazard statements | Classification procedure | | |
|---|--|--------------------------|--|--|
| Skin corrosion/irritation (Skin Corr. 1B) | H314: Causes severe skin burns and eye damage. | | | |

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

| Hazard statements | | | |
|-------------------|--|--|--|
| H290 | May be corrosive to metals. | | |
| H302 | Harmful if swallowed. | | |
| H314 | Causes severe skin burns and eye damage. | | |
| H318 | Causes serious eye damage. | | |
| H335 | May cause respiratory irritation. | | |
| H412 | Harmful to aquatic life with long lasting effects. | | |

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

| * [| ata | changed | compared | with | the | previous | version. |
|-----|-----|---------|----------|------|-----|----------|----------|
|-----|-----|---------|----------|------|-----|----------|----------|