



FIA

Fix All Aktivator

AKTIVATOR FOR FIX ALL GLUES

- Promotes and accelerates the curing time of cyanoacrylate glues
- Makes adhesion on porous materials such as wood possible
- Increases the bonding strength
- To be used in combination with Fix All, Fix All Flexible and Fix All 2K



General Information

FIX ALL AKTIVATOR is an activator for cyanoacrylate glues which promotes and fastens the curing time. FIX ALL AKTIVATOR dries out quickly and increases the bonding strength.

FIX ALL AKTIVATOR is resistant to solvents, oils, benzene, temperature fluctuations and atmospheric conditions. FIX ALL AKTIVATOR joints have a high tensile shear strength and show no shrinkage.

Technical Information

Chemical base: reactive DMPT activator and aliphatic hydrocarbons
Form: aerosol
Colour: transparent
Initial boiling point: -44°C
Flash point: -97°C
Lower explosion limit: 0,8 Vol %
Upper explosion limit: 10,9 Vol %
Vapour pressure (at 20°C): 8300 hPa

Density (at 20°C): 0,64 g/cm³
Organic solvents: 99,8 %
Pressure (at 20°C): 2 bar
Delivery rate (at 20°C): 0,5 g/sec
Application temperature: 10°C - 35°C
Storage: cool and dry
Shelf life: 12 months

Application and Use

- FIX ALL AKTIVATOR provides an exceptionally strong bond between almost all kinds of materials, with the exception of polyethylene, polypropylene and fluorine containing materials. Materials which can be bonded with FIX ALL AKTIVATOR: ABS, aluminium, bakelite, bronze, buthyl, celluloid, chloroprene, chrome, delrin, glass, copper, natural rubber, NBR, neoprene, nitril, nylon, phenol, polycarbonate, polystyrene, porcelain, hard pvc, stainless steel.
- On porous materials we recommend using FIX ALL AKTIVATOR.

Article nr	Name	Content	Section
X501012	Fix All Aktivator	150ml	ADHESIVES AND SEALANTS



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Xintex is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Xintex products provide, relates only to the standard conditions of sale of this product. In no case Xintex can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

TECH-MASTERS TRADING GMBH

Perfektastraße 55, 1230 Wien, Austria, Tel +43 (0) 1 / 867 29 07
Fax +43 (0) 1 / 867 29 93, E-Mail office@tech-masters-trading.com

WWW.XINTEX-GROUP.COM