



ANCHORING QUICK BICOMPONENT

- Polyurethane anchoring
- Excellent on walls with solid bricks and hollow partition bricks
- Ideal for light loads
- Quick
- Paintable
- Economical use



FIE

Fix It Easy

General Information

FIX IT EASY is a two-component, polyurethane-based adhesive that polymerises at ambient temperature. It has been studied for use in light, fast anchorage on walls with solid bricks or hollow partition bricks, concrete, cellular concrete, plasterboard and wood.

FIX IT EASY is the secure fixing solution for walls with hollow partition bricks; the speed of catalysis allows for considerable time-saving. Thanks to its composition, FIX IT EASY also adheres to many synthetic materials such as PVC, ABS, Plexi, etc.

Technical Information

FIX IT EASY (Part A):
Physical state: paste
Colour: brown
Odour: mild
Density: 1.21 g/cm³
Water solubility: practically insoluble
Dynamic viscosity: 27 Pa*s

FIX IT EASY (Part B):
Physical state: Paste
Colour: Brown
Odour: mild
Water solubility: practically insoluble
Dynamic viscosity: 22 Pa*s
Density: 1.2 g/cm³

Base: Polyurethane
Mixing ratio, volume: 1:1
Mixing ratio, weight: 0.89:1
Thermostability: -37°C/+100°C
Application temperature: +10°C/+30°C
Tensile strength (at 23°C): 20 MPa
Elongation at break: 15%
Shore D hardness: 70
Resistivity: 1.2x10¹² Ohm*cm
Open time: 1 minute
Setting time: 5 minutes
Final catalysis: 4 hours

Application and Use

- FIX IT EASY is suitable for the rapid installation of small equipment such as boilers, electrical panels, shutters, gates, shelves, kitchen furniture, etc.
- FIX IT EASY is not a structural chemical anchoring.
- For use on walls with hollow bricks, we recommend the use of coverings. The holes must be clean, dry and free of dust; to obtain excellent cleaning results, clean the hole with a wire brush and subsequently blow with a pump. On very dusty materials, it is recommended that the operation is repeated several times.

Article nr	Name	Content	Shelf Life	Catalog
X915050	Fix It Easy white	50ml	see imprint + 18 months	ADHESIVES AND SEALANTS



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Xintex is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Xintex products provide, relates only to the standard conditions of sale of this product. In no case Xintex can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

TECH-MASTERS TRADING GMBH

Perfektastraße 55, 1230 Wien, Austria, Tel +43 (0) 1 / 867 29 07
Fax +43 (0) 1 / 867 29 93, E-Mail office@tech-masters-trading.com

WWW.XINTEX-GROUP.COM