

MULTIPURPOSE H1 LUBRICANT FOR FOOD INDUSTRY

- colourless
- reduces friction and wear
- dirt and water repellent
- resistant to hot and cold water
- · protects against corrosion
- long service live



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Xintex is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Xintex products provide, relates only to the standard conditions of sale of this product. In no case Xintex can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

TECH-MASTERS TRADING GMBH

Perfektastraße 55, 1230 Wien, Austria, Tel +43 (0) 1 / 867 29 07 Fax +43 (0) 1 / 867 29 93, E-Mail office@tech-masters-trading.com



General Information

FOOD GEL is a physiologically harmless multipurpose grease that meets the requirements for a lubricant in food processing. FOOD GEL resists water and salt solutions in operating temperatures of -15 °C to +130 °C. In contact of lubricant with food or

Technical Information

Physical state: pasty Colour: colourless Odour: odourless Thickener: Inorganic Base oil: Medical white oil, synthetic KW Base oil viscosity at 40 °C: Approximately 200 mm²/s Viscosity index: > 100

Application and Use

Appliaton:

FOOD GEL is used in all types of food establishments in the manufacturing, processing, storage and final preparation of food and beverage.

FOOD GEL is widely used in meat factories, canneries, bakeries, kitchens and restaurants, dairies, bottling plants, food warehouses and breweries. Furthermore, it is used in water plants, agriculture, forestry and in other companies, where the use of conventional lubricants and their eventual release into the environment could cause environmental damage or accidents

FOOD GEL can be used for lubrication of rolling bearings, plain bearings and other mechanical parts.

Article nr Name X502005 Food Gel







with a raw material, must be contaminated part removed and cannot be used for human con-sumption.

Service temperature range: -15 °C to +130 °C (briefly

• Use:

Shelf Life

see imprint + 36 months

Thoroughly clean the places to be lubricated first. Apply thinly and and evenly to the parts to be lubricated. Fill roller bearings only to a maximum of 80%. Only fill to 60% of the bearing volume at most in the high temperature range (observe the rules laid down by the bearing maker).

Catalog

LUBRICANTS

FOOD GEL is biodegradable over 90% and offers a very good lubricating and durability. It also features excellent anticorrosive and protective properties.

+150 °C) Initial boiling point and boiling range: 218 °C Flash point: 170 °C VKA: 2,200 N Density (at 20 °C): 0.9 g/cm3 Water solubility: practically insoluble Safety measures: consult the Safety Data Sheet.

Content

400g





Food Gel