



MLSE

Multi Fix LSE

DOUBLE SIDED TAPE FOR EASY AND IMMEDIATE MOUNTING

- Extremely high ultimate adhesion.
- Tearable by hand.
- Suited for high load bearing applications.
- Easy and immediate mounting of all kind of objects (e.g. nameplates, hooks, kitchen utensils, etc.)



General Information

MULTI FIX LSE is a double sided tape which combines an excellent internal strength at elevated temperatures with a good tack and an extremely high ultimate adhesion to various substrates.

The polyester fabric provides strength and makes the tape tearable by hand. MULTI FIX LSE is very well suited for high load bearing applications to smooth and rough surfaces

Technical Information




Adhesive: Synthetic rubber
Carrier: Polyester fabric, Semi transparent
Liner: Polypropylene, Blue
Thickness: 0,80 mm
Adhesive strength, open side: 55 N/25 mm
Adhesive strength, covered side: 40 N/25 mm
Tensile strength: 80 N/ 25 mm
Static shear: 3kg at 23°C for > 168h
Service temperature range: -10°C to +75°C

Storage: Clean and dry in a well ventilated area, preferably at a temperature between +15°C and +30°C. Stored under these conditions shelf life will be a minimum of one year.
Chemical resistance: Limited
UV resistance: Limited
Ageing resistance: Good
Plasticizer resistance: Limited
Suitable for LSE: Yes

Application and Use

- Usage temperature should be between + 15°C and + 30°C.
- Surface must be clean and free from dust and grease.
- Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level.
- The indicated level of performance will be reached after a bonding period of 24 HRS at 23 °C.

Article nr	Name	Content	Section
X591019	Multi Fix LSE 19mm x 10m	1 pc.	TAPES



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

TECH-MASTERS TRADING GMBH

Perfektastraße 55, 1230 Wien, Austria, Tel +43 (0) 1 / 867 29 07
Fax +43 (0) 1 / 867 29 93, E-Mail office@tech-masters-trading.com

WWW.XINTEX-GROUP.COM