

SPRAYABLE ANTI SLIP COATING

- Makes all surfaces anti-slip
- Transparent colour
- Simple, time saving application
- Removable
- Good UV resistance
- Part-time and permanent use
- Can be colored with acrylic paint



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Xintex is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Xintex products provide, relates only to the standard conditions of sale of this product. In no case Xintex can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

TECH-MASTERS TRADING GMBH

WWW.XINTE<mark>X-G</mark>ROUP.COM

Perfektastraße 55, 1230 Wien, Austria, Tel +43 (0) 1 / 867 29 07 Fax +43 (0) 1 / 867 29 93, E-Mail office@tech-masters-trading.com



POG

GENERAL INFORMATION

POWER GRIP SPRAY is a transparent coating with anti-slip-particles. POWER GRIP SPRAY is ideal for floors, steps, balustrade, handles and all other applications where surfaces have to be prepared with a safe grip.

TECHNICAL INFORMATION

Form: Aerosol Color: Colorless Odor: Characteristic Degree of gloss: (at measurement angle 60° acc. to DIN 67530) glossy: >15 gloss units Efficiency: Depending on consistence and color of the ground: 500 ml are sufficient for 1,5 - 2,5 m² Drying time (at 20°C, 50% relative air humidity): Dust-dry: after approx. 10 minutes Dry to touch: after approx. 30 minutes Ignition temperature: 333°C Lower explosion limit: 1 Vol% Upper explosion limit: 13 Vol%

APPLICATION AND USE

- The surface must be clean, free of gease and dust
- Shake can carefully for 2 minutes
- Carry out spray for testing.

Article nr

X166001

• The structural density and effect is depending on the number of coats and the spraying distance

Power Grip Spray

Name

surfaces like cement, stone, screed, asphalt, clinker, ceramictile, metal and so on. POWER GRIP SPRAY is your product for preparing a safe and anti-slip surface.

Vapour pressure (at 20°C): 8300 hPa (6225,5 mm Hg) Density (at 20°C): 0,75 g/cm³ Organic solvents: 88% VOC-content: 660,0 g/l (88,01%) Solids content: 12% The drying time depends on surrounding temperature, air humidity and thickness of the applied coat. Temperature resistance: to 80°C UV resistance: good Shelf life: 10 years if appropriate storage provided (= 10°C - 25°C, relative air humidity of max. 60%

- Apply several thin layers
- Can be colored with all acrylic paints (wet in wet)
 Power Grip Spray can be removed by Graffitex or Megasolv

Content Section 400ml SURFACE PROTECTION AND TREATMENT







SURFACE PROTECTION AND TREATMENT

For all out- and indoors applications and for most

Power Grip Spray