



PXC

Polar-X Clean

HIGH PERFORMANCE CLEANER AND DEGREASER

- The aerosol can enables effective cleaning of even hard-to-reach areas with a powerful spray jet
- Safe to use on all metals and most plastics
- Cleans and degreases within seconds
- Evaporates quickly and leaves no residue
- Excellent for cleaning brakes and carburetors and applications requiring a completely dry and clean surface
- Recommended as a surface cleaner prior to using adhesives, paints, and tapes, ...
- Surface can be painted after just one minute
- FREE OF
- PTFE/PFAS
- SILICONE
- SVHC



General Information

POLAR-X CLEAN is a highly effective cleaner and degreaser designed for the rapid and thorough removal of grease, oil, dirt, and dust. It is easy to apply, works quickly, and is economical in use. Thanks to its targeted spray, POLAR-X CLEAN ensures efficient cleaning even in hard-to-reach areas. The product cleans and degreases metals, glass, ceramics, textiles, and many plastics, effectively removing all oil and grease stains without leaving residues.

For stubborn residues, allow POLAR-X CLEAN to penetrate for a short time and then spray again.

Key Benefits: Fast and thorough action, Residue-free drying, Efficient even in hard-to-reach areas, Suitable for a wide range of materials

Technical Information

POLAR -X-CLEAN AEROSOL
 Colour: colourless
 Odour: characteristic
 Initial boiling point: 36°C (109-66-0 Pentane)
 Pressure (at 20°C): 5 - 5,5 bar
 Flash point: -26°C
 Lower explosion limit: 0,6 Vol%
 Upper explosion limit: 13,0 Vol%
 Ignition temperature: > 200°C
 Vapour pressure (at 20°C): 246 hPa
 Density (at 20°C): 0,75 g/cm³
 Kinematic viscosity (40°C): ≤ 20.5 mm²/s
 Organic solvents: 96,0%
 Application temperature: 10 - 35°C
 Shelf life: 12 months
 Storage: cool (10 - 20°C) and dry

POLAR -X-CLEAN LIQUID
 Colour: colourless
 Odour: characteristic
 Boiling range: 55,8 - 56,6°C
 Flash point: < -18°C
 Lower explosion limit: 0,6 Vol%
 Upper explosion limit: 13 Vol%
 Vapour pressure (at 20°C): 246 hPa
 Density (at 20°C): 0,72 g/cm³
 Organic solvents: 100%
 Application temperature: 10 - 35°C
 Shelf life: 12 months
 Storage: cool (10 - 20°C) and dry


Application and Use

- **APPLICATION:**
- The versatility of POLAR-X CLEAN makes it an ideal cleaner for use in industry, trade, repair, and assembly.
- It is also highly effective in the automotive sector, for example on:
 - Brakes (drum and disc brakes)
 - Clutches (linings and components)
 - Engine components, sensors, and much more
- **USE:**
- Do not use on hot parts
- Use at room temperature and shake well before use
- Spray directly onto the surface to be cleaned
- In some cases, allow the product to act for a short time
- If necessary, wipe off with a clean cloth
- Allow to evaporate/dry
- **IMPORTANT:** Please test the product in a concealed area first. Cleaner may damage paint and some plastics!

Article nr	Name	Content	Shelf Life	Catalog
X499001	Polar-X Clean 500ml	500ml	see imprint + 36 months	CLEANERS AND DEGREASERS
X499005	Polar-X Clean 5l	5l	see imprint + 36 months	CLEANERS AND DEGREASERS
X875004	Spray Master Acid 1,5l	1pc.	-	TOOLS
Y390302	Glove GoGrip NI M	50 pcs.	-	HEALTH AND SAFETY
Y899050	Cleaning Cloth small 2-ply	1 roll	-	TOOLS
Y899201	Wall Holder	1pc.	-	TOOLS

Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Xintex is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Xintex products provide, relates only to the standard conditions of sale of this product. In no case Xintex can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



TECH-MASTERS TRADING GMBH

Perfektastraße 55, 1230 Wien, Austria, Tel +43 (0) 1 / 867 29 07
 Fax +43 (0) 1 / 867 29 93, E-Mail office@tech-masters-trading.com

WWW.XINTEX-GROUP.COM

