



## SGP

## Slip Grip

## STOPS SLIPPING RELIABLY

- Can be used on all types of flat-ribbed, V-belts and conveyor belts
- Reduces slippage
- Cleans and conditions
- Highly adhesive
- Extends belt life
- Not harmful to canvas, leather or rubber
- NSF approved for food industry



## General Information

SLIP GRIP is a clear and tacky lubricant, that eliminates irritating belt squeal and recovering of lost traction and belt slippage. SLIP GRIP is used to increase the transcription of drivebelts and transport belts. SLIP GRIP puts a stop to cracks, squeaking and repels dirt, dust and grease.

SLIP GRIP is suitable for all kinds of belts, like, types of flat-ribbed, V-belts and conveyor belts, despite of size or transmission speed. SLIP GRIP is safe to use on leather, rubber, canvas, silicones and all kinds of materials of belts.

## Technical Information


Base: Solvents, highly tacky lubricants, polymers  
Propellant: Carbondioxide  
Apperance: Clear liquid, tacky layer after drying

Pressure(20°C): 4 Bar  
Spray pattern: Mist, tacky coating  
Color: Colorless

## Application and Use

- Recommended application temperature for SLIP GRIP is approximately 25°C.
- For best results shake the can well before use.
- SLIP GRIP should be spread while the engine is idling. Spray SLIP GRIP lightly on inner working surface of belt.
- With SLIP GRIP only a uniform thin coat is sufficient.
- After application allow the belt to run for several minutes and avoid excessive amount.
- SLIP GRIP can be used in all industries, for example production industry, food industry, automotive industry etc...
- Applications: forklifts, cooler trucks, floor cleaning machines, drive belts, conveyor belts,...

Article nr	Name	Content	Section
X132501	Slip Grip	500ml	LUBRICANTS



## Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Xintex is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Xintex products provide, relates only to the standard conditions of sale of this product. In no case Xintex can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

## TECH-MASTERS TRADING GMBH

Perfektastraße 55, 1230 Wien, Austria, Tel +43 (0) 1 / 867 29 07  
Fax +43 (0) 1 / 867 29 93, E-Mail office@tech-masters-trading.com

WWW.XINTEX-GROUP.COM