



SI

Super Impact

EXTRA HEAVY DUTY NON-MELT GREASE

- High Temperature Grease. Will stay in place at extremely high temperatures, in excess of 290°C.
- Clings to metal surfaces and coats them with an exclusive plating action.
- Withstand high pressures and heavy shock load.
- Strongly resists bleeding. Exclusive anti-wear additives provide exceptionally long lasting performance.
- Will not flush out by heavy rain. Provides complete, waterproof protection.
- Offers excellent protection against rust, corrosion, and wear.
- Is resistant to most acids, weather, salt spray, steam, oxidation and dirt.



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Xintex is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Xintex products provide, relates only to the standard conditions of sale of this product. In no case Xintex can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

General Information

SUPER IMPACT is an extra heavy duty non-melt grease specially formulated from the highest quality paraffin base oils and special additives which enables it to withstand

the heavy impact and pounding pressures of equipment operating under boundary conditions without splattering. The grease stays in place without pounding out of the fitting or bearing.

Technical Information

Physical state: pasty
Colour: red
Odour: characteristic
Thickening agent: Bentonit (no mixing with other greases)
Density (20 °C): 0,87g/cm³
Flash point: > 100°C, ISO 3679
Initial boiling point and boiling range: 100 °C
Water solubility: practically insoluble
VKA: 3500 N
Water Resistance: Excellent

Rust Resistance: Excellent
Acid Resistance: Excellent.
Conductivity: Non-Conductive
NLGI Grade: 2.5
Shelf life: 12 month, always keep the lid closed, store under shade away from direct heat.
Safety measures: consult the Safety Data Sheet.
FOR PROFESSIONAL USE ONLY!

Application and Use

- SUPER IMPACT is recommended for use in: plain and anti-friction bearings, sleeve bearings, universal joints, water pumps, wheel bearings, drive shafts, spines, chains, chassis, 5th wheels, king pins and disc brakes.
- Reduces Downtime and maintenance labor because of smooth, cool performance.
- Outperforms and outlasts conventional greases in everyday lubrication functions. It is a lubricant formulated for the most severe operating conditions.
- Inventory is reduced with one superior quality, multi-purpose lubricant.
- Life of equipment is increased and maintenance costs reduced.

Article nr	Name	Content	Shelf Life	Catalog
X502001	Super Impact	400g	see imprint + 24 months	LUBRICANTS
X502002	Super Impact	20kg	see imprint + 24 months	LUBRICANTS
X502004	Super Impact	5kg	see imprint + 24 months	LUBRICANTS

