according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 17 Aug 2023 Print date: 27 Feb 2024

Version: 2

Page 1/12
Slix 5



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Slix 51

Article No.:

X201005

UFI:

0DDW-SGTH-F1A6-YXWU

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Lubricating agent

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3 4653 Eberstalzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (Flam. Liq. 2)	H225: Highly flammable liquid and vapour.	
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



GHS02 Flame

 $\langle ! \rangle$

GHS07 Exclamation mark



GHS08 Health hazard



GHS09 Environment

Signal word: Danger

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 17 Aug 2023 Print date: 27 Feb 2024

Version: 2 Page 2/12



Slix 5l

Hazard components for labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane; Hydrocarbons, C7, n-alkanes, isoalkanes, cyclene

Hazard statements	for physical hazards
H225	Highly flammable liquid and vapour.

Hazard statements for health hazards		
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H336	May cause drowsiness or dizziness.	

Hazard statements for environmental hazards		
H411	Toxic to aquatic life with long lasting effects.	

Supplemental hazard information		
EUH066	Repeated exposure may cause skin dryness or cracking.	

Precautionary statements Prevention		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P243	Take action to prevent static discharges.	
P261	Avoid breathing vapours.	
P271	Use only outdoors or in a well-ventilated area.	
P273	Avoid release to the environment.	
P280	Wear protective gloves.	

Precautionary statements Response		
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.	
P302 + P352	IF ON SKIN: Wash with plenty of water.	
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P312	Call a POISON CENTER/doctor if you feel unwell.	
P331	Do NOT induce vomiting.	
P332 + P313	If skin irritation occurs: Get medical advice/attention.	

Precautionary statements Storage		
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.	

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Additional information:

aliphatic hydrocarbons >= 30%

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 17 Aug 2023 Print date: 27 Feb 2024

Version: 2

Page 3/12
Slix 5



Hazardous ingredients / Hazardous impurities / Stabilisers:

ideal dods mg. calcines / maear dods impartices / otabilisers:		
Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
EC No.: 921-024-6 REACH No.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), STOT SE 3 (H336), Skin Irrit. 2 (H315) Other Danger	25 - < 50 Vol-%
CAS No.: 64742-49-0 EC No.: 927-510-4 REACH No.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclene Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), STOT SE 3 (H336), Skin Irrit. 2 (H315) Other Danger	25 - < 50 Vol-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation:

Remove person to fresh air and keep comfortable for breathing. When in doubt or if symptoms are observed, get medical advice.

In case of skin contact:

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. When in doubt or if symptoms are observed, get medical advice.

After eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If symptoms occur or persist, consult an ophthalmologist.

Following ingestion:

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

Self-protection of the first aider:

First aider: Pay attention to self-protection!

4.2. Most important symptoms and effects, both acute and delayed

Headache, Nausea, Dizziness, Fatigue, Skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water mist, Foam, Carbon dioxide (CO2), Extinguishing powder

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis can produce gases of varying toxicity. In the case of products containing hydrocarbons, e.g. CO, CO2, aldehydes and soot. These can be very dangerous if inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

Do not inhale explosion and combustion gases. Move undamaged containers from immediate hazard area if it can be done safely.

In case of fire: Wear self-contained breathing apparatus.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 17 Aug 2023 Print date: 27 Feb 2024

Version: 2

Page 4/12
Slix 5



SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. First aider: Pay attention to self-protection!

Protective equipment:

Wear personal protection equipment (refer to section 8).

6.1.2. For emergency responders

Personal protection equipment:

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment:

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up:

Clean contaminated articles and floor according to the environmental legislation.

Other information:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Further information on proper storage: see section 7.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Observe instructions for use. Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. When using do not eat, drink, smoke, sniff. Wear personal protection equipment (refer to section 8).

Fire prevent measures:

Keep away from sources of ignition - No smoking.

Advices on general occupational hygiene

Avoid exposure - obtain special instructions before use. Wear suitable work clothing. Draw up and observe skin protection programme. Avoid contact with eyes and skin.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Keep container tightly closed. Observe legal rules and regulations.

Hints on storage assembly:

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Food and feedingstuffs.

Storage class (TRGS 510, Germany): 3 - Flammable liquids

Further information on storage conditions:

Protect from frost. Protect from direct sunlight. Store in a cool dry place. The official regulations for the storage of pressurised gas packages must be observed.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 17 Aug 2023 Print date: 27 Feb 2024

Version: 2



Page 5/12 Slix 5

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
MAK (AT)	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclene CAS No.: 64742-49-0 EC No.: 927-510-4	 200 mL/m³ 400 mL/m³ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/ Isohexanen von weniger als 25 %)
MAK (AT)	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclene CAS No.: 64742-49-0 EC No.: 927-510-4	 170 mL/m³ 340 mL/m³ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/ Isohexanen von 25 % oder mehr)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6	2,035 mg/m ³	① DNEL worker ② Long-term – inhalation, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6	608 mg/m ³	① DNEL Consumer ② Long-term – inhalation, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6	773 mg/kg bw/ day	DNEL worker Long-term - dermal, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6	300 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6	699 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6	699 mg/kg bw/ day	DNEL Consumer Long-term - oral, systemic effects
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclene CAS No.: 64742-49-0 EC No.: 927-510-4	2,085 mg/m ³	① DNEL worker ② Long-term – inhalation, systemic effects
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclene CAS No.: 64742-49-0 EC No.: 927-510-4	477 mg/m³	① DNEL Consumer ② Long-term – inhalation, systemic effects

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 17 Aug 2023 Print date: 27 Feb 2024

Version: 2

Page 6/12



Slix 5I

Substance name	DNEL value	DNEL type Exposure route
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclene CAS No.: 64742-49-0 EC No.: 927-510-4	300 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclene CAS No.: 64742-49-0 EC No.: 927-510-4	149 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclene CAS No.: 64742-49-0 EC No.: 927-510-4	149 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects

8.2. Exposure controls

8.2.1. Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

8.2.2. Personal protection equipment







Eye/face protection:

Suitable eye protection: Safety goggles with side shields (EN 166).

Skin protection:

Hand protection:

Preventive skin protection through the use of skin protectants is recommended. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Glove material: NBR (Nitrile rubber) Breakthrough time: 480 min

Thickness of the glove material: 0,45 mm

EN ISO 374

Body protection:

Wear suitable protective clothing when working. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection:

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

If the relevant occupational exposure limits are exceeded, the following must be observed: Suitable respiratory protective device: Combination filter device (DIN EN 141). Filter unit with filter or blower filter unit type: A

Observe the wear time limits as specified by the manufacturer.

Observe legal rules and regulations.

8.2.3. Environmental exposure controls

Observe legal rules and regulations.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Colour: colourless

Odour: characteristic

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 17 Aug 2023 Print date: 27 Feb 2024

Version: 2 Page 7/12



Slix 5l

Safety relevant basis data

Parameter	Value	at °C	① Method
			② Remark
рН	No data available		
Melting point	No data available		
Freezing point	No data available		
Initial boiling point and boiling range	65 °C		
Flash point	-26 °C		① ISO 3679
Evaporation rate	No data available		
Auto-ignition temperature	No data available		
Upper/lower flammability or explosive limits	1.1 - 7.4 Vol-%		
Vapour pressure	No data available		
Vapour density	No data available		
Density	0.7 g/cm ³	20 °C	① DIN 51757
Bulk density	not applicable		
Water solubility	No data available		
Dynamic viscosity	No data available		
Kinematic viscosity	< 7 mm ² /s	40 °C	① DIN EN ISO 3104

9.2. Other information

The data refer to the technical active substance: relative density, colour, odour, viscosity, pH-value.

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Direct sunlight, heat, open flames, sparks, hot surfaces, sources of ignition.

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis can produce gases of varying toxicity. In the case of products containing hydrocarbons, e.g. CO, CO2, aldehydes and soot. These can be very dangerous if inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane	EC No.: 921-024-6
LD₅₀ oral: >5,000 mg/kg (Rat) OECD 401	
LD ₅₀ dermal: >2,920 mg/kg (Rabbit)	
LC ₅₀ Acute inhalation toxicity (gas): >20 ppmV 4 h (Rat) OECD 403	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 17 Aug 2023 Print date: 27 Feb 2024

Version: 2

Page 8/12



Slix 5l

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclene CAS No.: 64742-49-0 EC No.: 927-510-4

LD₅₀ oral: ≥5,000 mg/kg (Rat) **LD₅₀ dermal:** >2,920 mg/kg (Rat)

LC₅₀ Acute inhalation toxicity (vapour): >23.3 mg/L 4 h (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Causes skin irritation.

Serious eve damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

May be fatal if swallowed and enters airways.

Additional information:

No data available

11.2. Information on other hazards

Endocrine disrupting properties:

This product contains a substance that has endocrine disrupting properties with respect to non-target organisms.

SECTION 12: Ecological information

12.1. Toxicity

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6

LC₅₀: 11.4 mg/L 4 d (fish, Oncorhynchus mykiss) OECD 203

EC₅₀: 3 mg/L 2 d (crustaceans, Daphnia magna) OECD 202

NOEC: 0.17 mg/L 21 d (crustaceans, Daphnia magna)

LOEC: 0.32 mg/L 21 d (crustaceans, Daphnia magna)

EC₅₀: 30 - 100 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclene CAS No.: 64742-49-0 EC No.: 927-510-4

 LC_{50} : >13.4 mg/L (fish)

EC₅₀: 3 mg/L (crustaceans, Daphnia magna))

NOEC: 0.17 mg/L (Algae/water plant, Daphnia magna)

LOEC: 0.32 mg/L (Algae/water plant)

Aquatic toxicity:

Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 17 Aug 2023 Print date: 27 Feb 2024

Version: 2

Page 9/12



Slix 5l

Assessment/classification:

No further relevant information available.

12.2. Persistence and degradability

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6

Biodegradation: Yes, rapidly

Abiotic degradation:

No further relevant information available.

12.3. Bioaccumulative potential

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane	EC No.: 921-024-6
Log K _{OW} : 5.2	
Bioconcentration factor (BCF): 250	

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycle	ne, <5% n-hexane	EC No.: 921-024-6
Results of PBT and vPvB assessment: —		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclene	CAS No.: 64742-49-0	EC No.: 927-510-4
Results of PBT and vPvB assessment: —		

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product contains a substance that has endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

07 07 04 * other organic solvents, washing liquids and mother liquors

*: Evidence for disposal must be provided.

Waste code packaging

15 01 10 * packaging containing residues of or contaminated by dangerous substances *: Evidence for disposal must be provided.

Wasta traatment entions

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Uncleaned packaging: Water (with cleaning agent). Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)		Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1268	UN 1268	UN 1268	UN 1268

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 17 Aug 2023 Print date: 27 Feb 2024

Version: 2 Page 10/12



Slix 5l

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.2. UN proper ship	oping name		
PETROLEUM PRODUCTS, N.O.S. (Hydrocarbons, C6- C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane) 14.3. Transport haza	PETROLEUM PRODUCTS, N.O.S. (Hydrocarbons, C6- C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane)	PETROLEUM PRODUCTS, N.O.S. (Hydrocarbons, C6- C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane)	PETROLEUM PRODUCTS, N.O.S. (Hydrocarbons, C6- C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane)
3 14.4. Packing group	3	3	3
	lii	II	II
14.5. Environmenta	hazards		
(L)	¥2>	MARINE POLLUTANT	
14.6. Special precau	itions for user		
Special Provisions: 640C 664	Special Provisions: 363 640C	Special Provisions:	Special Provisions:
Limited quantity (LQ):	Limited quantity (LQ):	Limited quantity (LQ):	Limited quantity (LQ):
Excepted Quantities (EQ):	Excepted Quantities (EQ):	Excepted Quantities (EQ):	Excepted Quantities (EQ):
Hazard identification number (Kemler No.): 33 Classification code: F1 Tunnel restriction code: (D/E)	Classification code: F1	EmS-No.: F-E, S-E	Remark: IATA Packing Instructions - Passenger: 353 IATA Maximum Quantity - Passenger: 5 L IATA- Verpackungsanweisung - Cargo: 364 IATA Maximum Quantity - Cargo: 60 L

14.7. Maritime transport in bulk according to IMO instruments not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Restrictions on use:

Restrictions on use (REACH, Annex XVII) Entry 3, Entry 28, Entry 40

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 17 Aug 2023

Version: 2

Print date: 27 Feb 2024



solutions for professionals

Page 11/12

Slix 51

16.2. Abbreviations and acronyms

American Conference of Governmental Industrial Hygienists

European Agreement concerning the International Carriage of Dangerous Goods by Inland ADN

Waterways

European Agreement concerning the International Carriage of Dangerous Goods by Road **ADR**

AOX Adsorbable Organic halogen compounds

BCF Bioconcentration Factor CAS Chemical Abstracts Service

Classification, Labelling and Packaging CLP

DIN German Institute for Standardization / German Industrial Standard

DNEL derived no-effect level Effective Concentration 50% EC_{50}

ΕN European Standard Exposure scenario ES

EWC European Waste Catalogue

International Civil Aviation Organization **ICAO** International Maritime Dangerous Goods **IMDG** IMO International Maritime Organization ISO International Standards Organisation

KG body weight

 LC_{50} Lethal (fatal) Concentration 50%

Lethal (fatal) Dose 50% LD_{50}

Maximum concentration in the workplace air (CH) MAK

National Fire Protection Association **NFPA**

NIOSH National Institute for Occupational Safety & Health

NOEC No Observed Effect Concentration

OECD Organisation for Economic Cooperation and Development

OSHA Occupational Safety & Health Administration persistent and bioaccumulative and toxic PBT

PNEC Predicted No Effect Concentration

Registration, Evaluation and Authorization of Chemicals REACH Dangerous goods regulations for transport by rail RID

Technische Regeln für Gefahrstoffe **TRGS**

UN **United Nations**

ZNS central nervous system

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (Flam. Liq. 2)	H225: Highly flammable liquid and vapour.	
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 17 Aug 2023 Print date: 27 Feb 2024

Version: 2 Page 12/12 XINTEX

solutions for professionals

Slix 51

Hazard statements	
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.