



SLH

Slx H1

**COLORLESS, UNIVERSAL
SILICONE OIL FOR FOOD
INDUSTRY**

- NSF H1-certified
- Especially suitable for the use in food, pharmaceutical and textile industries
- Colourless and odourless
- Low viscosity
- Waterresistant for continuous lubrication
- Can be used as a release agent for moulds, etc.
- Safe for the use on metal and non-metal surfaces
- Based on 100 % pure silicone oil

**General Information**

SLIX H1 - formulated to provide the best results in both lubricating and releasing. This low viscosity silicone oil enables you to effectively lubricate parts like rollers, conveyors, sliding doors and many more. Even the smallest cracks and gaps can easily be reached with SLIX H1. SLIX H1 is waterproof, colourless and odourless which makes it the perfect multi-purpose lubricant for most areas.

Especially for food, pharmaceutical and textile industries, this product offers high-quality and can safely be used due to its NSF H1 certification. SLIX H1 is used for lubricating metal and non-metal surfaces (e.g. guides, conveyors, cutting knives and plastic components) but you can also apply it into moulds as a release agent. Increase the work efficiency of your production with SLIX H1!

Technical Information



Physical state: aerosol
Odour: characteristic
Initial boiling point: -44,5°C
Flash point: -97°C
Auto-ignition temperature: 285 °C
Upper/lower flammability or explosive limits: 1.4 - 10.9 Vol-%
Vapour pressure (at 20°C): 3300 hPa

Density (at 20°C): 0,536 g/cm³
Water solubility immiscible
Operating temperature range: -30°C to 150°C
Application temperature: 15°C - 25°C
Storage: cool and dry
Shelf life: 24 months

Application and Use

- APPLICATION:
 - Universal lubricant for all kinds of application fields
 - Ideal for the use in food, pharmaceutical and textile industries (e.g. dairy factories, bakeries, breweries, cardboard manufacturing, abattoires,...)
 - Can be used on rollers, conveyor belts, graders, sliding doors, windows, office furniture, zippers and many more
 - Can be applied onto moulds as a release agent
- USE:
 - Shake the can well before use!
 - Keep a spraying distance of 15-20 cm
 - Spray evenly on the area to be treated
 - Apply SLIX H1 on clean parts which need lubrication - avoid excessive lubrication!
 - Do not apply the product on equipment while food is being processed or transported!
 - SLIX H1 should not be used on parts which are likely to be painted

Article nr	Name	Content	Shelf Life	Catalog
X201100	Slx H1 500ml	500ml	see imprint + 36 months	LUBRICANTS

**Notice**

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Xintex is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Xintex products provide, relates only to the standard conditions of sale of this product. In no case Xintex can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

TECH-MASTERS TRADING GMBH

Perfektastraße 55, 1230 Wien, Austria, Tel +43 (0) 1 / 867 29 07
Fax +43 (0) 1 / 867 29 93, E-Mail office@tech-masters-trading.com

WWW.XINTEX-GROUP.COM