



## SPS

## Spray Seal

**EASY SEAL-COATING SPRAY  
FOR IN- AND OUTDOOR  
AREAS**

- Fast-drying
- Excellent flexibility
- Easy to apply and repaint
- Excellent adhesion on porous surfaces
- Excellent weather- and UV-resistance
- For indoor and outdoor use
- High sealing and waterproofing potential
- High coverage

**General Information**

SPRAY SEAL is a high efficient and strongly adhesive filler with an elastic base for sealing leaks. Due to its weather- and UV-resistance SPRAY SEAL can be used on interior or exterior surfaces such as roofs, coverings, plastic

metal pipes and any other type of PVC pipe. SPRAY SEAL creates a waterproof and flexible layer that protects all types of surfaces once it has fully cured. SPRAY SEAL is free of bitumen and silicone.

**Technical Information**

Binder type: Special resin  
Physical state: Aerosol  
Base: styrol rubber  
Color: Black, grey  
Initial boiling point and boiling range: -25 °C  
Vapour pressure (50 °C): < 300 kPa  
Density (20 °C): 796 kg/m<sup>3</sup>  
Relative density (20 °C): 0.796  
Self ignition temperature: 240 °C  
Dry to the touch (ASTM D-1640 ISO 1517): 30 - 45min  
Total dry time (ASTM D-1640 ISO 1517): 24h (2 coats)  
Thickness of dry coat (ASTM D-823 ISO 2808): 30 µm/coat

Repainted\*: 30min  
Repainted with other paints\*: 24h  
Theoretical performance (continuous painting): 1-1,25 m<sup>2</sup>; 2 coats (60 µ) 0,6 - 0,75 m<sup>2</sup>  
Conditions of application:  
- Atmospheric temp.: 10°C - 35°C  
- Surface temp.: 5°C - 50°C  
- Max. Humidity.: 85% R.H.P  
Shelf life: 5 years (Correctly stored)  
\* Times may vary depending on thickness of coat.

**Application and Use**

- APPLICATION:
  - Due to the characteristics of the product, we recommend its use for the sealing, protection and waterproofing of horizontal and vertical surfaces both indoors and outdoors.
    - Terraces, balconies, roofs.
    - Metal or plastic pipes (drains, PVC pipes).
    - Waterproofing of wet areas (ponds, aquariums).
    - Inside stone, ceramic or wooden plant pots, etc.
- INSTRUCTIONS FOR USE
  - Prepare and properly clean the area to be sealed before applying the product, to ensure effective adhesion.
  - Shake the spray can well before use for about one minute after hearing the sound of the mixer ball.
  - Apply the product on the area you wish to repair and around it at a distance of 20-30 cm. Apply two or three coats for best results. Depending on the size of the crack, more coats may be necessary.
  - Repaint after 20-30 minutes with the same paint.
  - Invert the spray can to purge the valve after use. If the cap becomes clogged replace it with a new one.
  - Do not apply to plugged-in electronic equipment and use in well-ventilated areas.
  - Only use on dry surfaces!

Article nr	Name	Content	Shelf Life	Catalog
X539501	Spray Seal black	500ml	see imprint + 60 months	ADHESIVES AND SEALANTS
X539502	Spray Seal grey	500ml	see imprint + 60 months	ADHESIVES AND SEALANTS

**Notice**

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Xintex is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Xintex products provide, relates only to the standard conditions of sale of this product. In no case Xintex can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

**TECH-MASTERS TRADING GMBH**

Perfektastraße 55, 1230 Wien, Austria, Tel +43 (0) 1 / 867 29 07  
Fax +43 (0) 1 / 867 29 93, E-Mail office@tech-masters-trading.com

[WWW.XINTEX-GROUP.COM](http://WWW.XINTEX-GROUP.COM)