

Slippery protection

Easy application

• 3 colors – 2 sizes

High abbreviation resistance

Good adhesion on all surface

STP

GENERAL INFORMATION

SAFETY GRIP TAPE with high adhesion, is ideal for SAFETY anti-slip protection on smooth surfaces. GRIP TAPE can

TECHNICAL INFORMATION

Adhesive: Acrylic Base material: PVC sheet Grain material: aluminium oxide Colour: black, white, yellow/black Liner: No liner Thickness: 0,8 mm Adhesion to steel: 15,7 N/25 mm Tensile strength: 59 N/25 mm Elongation at break: 25%

APPLICATION AND USE

• USE

Temperature: between 0°C and +35°C. Surface must be clean and free from dust and grease. Avoid touching exposed adhesive surface of the tape, as this impairs the performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24h at +23°C.

Resistance to oil: Good Shelf life: Clean and dry in a well ventilated area, Stored under these conditions shelf life will be

Ideal for anti-slip protection on smooth surfaces. For industrial applications as well as for use at home. Indoor and outdoor useable.

Article	e nr	Name	Content	Section
Y5721	.01	Safety Grip Tape black	Roll 25 mm x 18 m	TAPES
Y5721	.02	Safety Grip Tape black	Roll 50 mm x 18 m	TAPES
Y5722	201	Safety Grip Tape white	Roll 25 mm x 18 m	TAPES
Y5728	311	Safety Grip Tape yellow/black	Roll 25 mm x 18 m	TAPES
Y5728	312	Safety Grip Tape yellow/black	Roll 50 mm x 18 m	TAPES











NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Xintex is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Xintex products provide, relates only to the standard conditions of sale of this product. In no case Xintex can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

TECH-MASTERS TRADING GMBH

Perfektastraße 55, 1230 Wien, Austria, Tel +43 (0) 1 / 867 29 07 Fax +43 (0) 1 / 867 29 93, E-Mail office@tech-masters-trading.com



Slip Stop Tape

TAPES

be used for both industrial applications as for home, both indoor and outdoor.

Service temperature range: +5°C to +50°C

preferably at a temperature between +10°C and +30°C. a minimum of one year. APPLICATION

Resistance to water: Good

WWW.XINTE<mark>X-G</mark>ROUP.COM