# MULTI-PURPOSE HIGH-PRESSURE AND HIGH-TEMPERATURE GREASE

- Water resistant
- Operate in wide temperature range up to 200

C.

• ISO 6743/9 BFEB 2



## Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Xintex is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Xintex products provide, relates only to the standard conditions of sale of this product. In no case Xintex can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

# Uni Grease

#### **GENERAL INFORMATION**

UG

UNI GREASE is made of carefully chosen basic oils strengthened by complex lithium soap. For improvement of operation properties they are refined by additives avoiding oxidation and corrosion and equally they contain high-pressure additive. UNI GREASE is strongly adhesive to metal surfaces. It

is characterized in optimal structure and wide range of consistences. Especially in NLGI 2 consistence the grease guarantees an excellent protection from moistness and agresive surroundings. In NLGI 2 consistence the grease is blue whilst in other consistences the colour is brown.

### **Technical Information**

Colour: Cyan Appearance at 20°C. :Soft Densityat 15°C: 883kg/m3 Odor: mild Flash Point: 280°C. Vapor pressure at 20°C: below0.01kPa Dropping Point: 240°C. Penetration-Class NLGI 2

## **APPLICATION AND USE**

 UNI GREASE is intended for lubrication of roller bearings operating under exacting conditons, especially bearings working under high pressure and temperatures in mobile machines as well as in industry. They are able to operate in wide range of temperatures.

Article nr	Name	Content	Section
X502006	Uni Grease	400 g	LUBRICANTS
X502007	Uni Grease	9 kg	LUBRICANTS

# TECH-MASTERS TRADING GMBH



