



VO-Old

Voltex II

NON-CORROSIVE SAFETY SOLVENT

- Replaces naphtha, carbon tetrachloride, and other highly toxic or flammable solvents.
- Non-corrosive, non-flammable and non-conductive. High dielectric constant makes it safe for high voltage equipment.
- Safe for skin - has no unpleasant odors or fumes.
- No condensation problems. Even under humid conditions, moisture will not condensate on surfaces because of controlled evaporation rate.
- Product is 100% volatile and leaves no oily residues when parts are rinsed with fresh VOLTEX II.
- Economical - saves costly hours of downtime because dirt-free motors run longer and are more power efficient.



GENERAL INFORMATION

VOLTEX II is a favorite for the effortless maintenance of the running high voltage electrical and mechanical parts without causing expensive downtime. It's ready to use, fast drying, non-conductive

and non-corrosive characteristics cleans and degreases power tools, electrical motors and other electro-mechanical equipment without fear of flammability or left on oily deposits which accumulate further dust.

TECHNICAL INFORMATION


Type: Fluid
 Colour: Colourless
 Odour: Characteristic
 Boiling point/Boiling range: 162 °C
 Flash point: 41 °C
 Ignition temperature: >200 °C
 Density at 20 °C: 0.8554 g/cm³

Organic solvents: 100.0 %
 VOC (EC) 855.4 g/l
 Shelf life: 12 month, always keep the lid closed.
 Store under shade away from direct heat.
 Safety measures: consult the Safety Data Sheet.

APPLICATION AND USE

- VOLTEX II cleans and degreases power tools, electrical motors, air-conditioning and refrigerating equipment, industrial equipment, elevators and escalators, printing equipment etc.
- May also be used to remove adhesives, resins, and also stains from clothing. May attack certain varnishes, rubbers and plastics - Test before use on these materials.
- Do not dip, soak or spray plastic parts (typewriter keys, housings, push-buttons, plastic insulators) with VOLTEX II until these parts have been completely tested for solvent effects. VOLTEX II may soften or dissolve certain types of plastics.
- Dip Cleaning:
 Place VOLTEX II in a metal tank with a tight cover to prevent evaporation loss. Soak parts or equipment to be cleaned in the dip tank for several minutes and agitate to loosen dissolved deposits. Remove parts and flush with a small quantity of fresh VOLTEX II to remove traces of dissolved grease from the dip tank.
- NEVER USE IN ENCLOSED OR UNVENTILATED AREAS.

Article nr	Name	Content	Shelf Life	Catalog
X205005	Voltex II	5l	see imprint + 36 months	ELECTRICAL CONNECTIONS



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Xintex is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Xintex products provide, relates only to the standard conditions of sale of this product. In no case Xintex can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

TECH-MASTERS TRADING GMBH

Perfektastraße 55, 1230 Wien, Austria, Tel +43 (0) 1 / 867 29 07
 Fax +43 (0) 1 / 867 29 93, E-Mail office@tech-masters-trading.com

WWW.XINTEX-GROUP.COM