

XIG

# Xinc Guard

# **METAL SURFACE PROTECTION WITH ZINC ALUMINUM APPEARANCE**

- · Provides glossy appearance due to aluminum and zinc particles
- · Perfect top coat with galvanized appearance after using XINC 240 or **XINC 720**
- Powerful adhesion to all sorts of metals
- Provides additional corrosion protection
- · Economical in use
- · Can be painted over with most common paints and lacquers

### **General Information**

XINC GUARD creates an even surface with good coverage with glossy zinc/aluminum appearance similar to hot dip galvanized surfaces. It offers additional corrosion protection for all metal surfaces with quick and easy application. A protective coating of 99,5% pure aluminum and zinc particles is formed after only one pass of spraying. Due to synthetic resin additives, the

fine aluminum and zinc particles adhere firmly to the base material. After applying, the resin vaporizes and leaves a coating of pure aluminum/zinc which melts onto the metal surface.

XINC GUARD has a good chemical resistance and adheres well on most lacquers, synthetic materials, ferrous and non-ferrous metals. XINC GUARD shows very good elasticity properties.

# **Technical Information**

Form: aerosol Colour: metallic Odour: characteristic Boiling point: -44,5°C Flash point: -97°C

Auto-ignition temperature: 365°C Lower explosion limit: 0,7 Vol% Upper explosion limit: 13,0 Vol%

Vapour pressure (at 20°C): 3800 hPa Density (at 20°C):  $\approx 0.826 \text{ g/cm}^3$ Organic solvents: 90,3% Solids content: 7,4%

Application temperature: 10°C - 25°C

## **Application and Use**

- Use XINC GUARD at room temperature and shake well before use.
- · Make sure that the surface or parts to be treated are clean, dry as well as free of oil and grease.
- Spray an even layer and let it dry.

Name

- AFTER USE: to clean the nozzle and to prevent blockage, hold the can upside down and spray until only gas is released.
- Usable as primer after welding in metal and steel construction, general maintenance, car body shops etc. Perfectly suitable to create a glossy galvanized appearance after welding and grinding of hot dip galvanized materials.

Article nr













### Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Xintex is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Xintex products provide, relates only to the standard conditions of sale of this product. In no case Xintex can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.







